

## HIGH LIFT PALLET MOVER



- Manoeuvrable and easy to use the High Lift Pallet Mover lifts up to 1000kg to a maximum of 820mm
- High quality and robust construction
- Ideal for loading and unloading pallets
- Available with fixed forks with wrapover legs or adjustable forks with wide straddle legs
- Manual or battery electric operation
- Quality British manufacture and design

### Technical Features:

**FIXED WRAPOVER FORKS** for use with Euro pallets, two way non reversible pallets without bottom boards, post and box pallets and stillages.

**ADJUSTABLE FORKS AND WIDE STRADDLE LEGS** for use with any type of pallet, including those with perimeter boards (GKN type) subject to internal straddle width and fork length. 1320mm between legs as standard.

- No scissor arm obstruction allows the pallet to be positioned over racking, machines or vehicles
- Can be used safely at any height
- Fitted with two total stop brakes as standard
- Increased footprint makes the units extremely stable at all heights
- All models fitted with a slow lowering valve to control lowering speed
- Heavy duty castor wheels run on sealed ball races are fitted with toe guards for added operator safety
- Battery electric model supplied with heavy duty 70amp/hr battery and separate 12 volt charger

## Technical Specification:

Machine Type			Fixed Wrapover Forks			Adjustable Forks with Straddle Legs		
Capacity KG	C Raised Height	Operation	Reference	Lift Speed	Weight KG	Reference	Lift Speed	Weight KG
700	820 820	Manual	HM-700-820-M HM-700-820-E	17 / stroke 6 sec / meter	140 199	HM-700-820-M-ADJ	17 / stroke 6 sec / meter	150 209
		Electric				HM-700-820-E-ADJ		
1000	820 820	Manual	HM-1000-820-M HM-1000-820-E	17 / stroke 6 sec / meter	250 270	HM-1000-820-M-ADJ	17 / stroke 6 sec / meter	260 335
		Electric				HM-1000-820-E-ADJ		
Load Centre		-	500			500		
Free Lift		-	820			820		
Closed Fork Height		-	90			50		
O/A H x W x L		Fx B xA	1220 x 700 x 1620			1220 x 1550 x 1620		
Fork length		D	1140			1000		
Width Across Forks		E	528			740 max		
Fork W x D		Q x G	160 x 50			80 x 40		
Width Between Legs		J/H	Inside 260 / Outside 480			1320 / 1520		
Castor Wheels			150 dia, 2 Braked			150 dia, 2 Braked		
Load Roller Dia x L			80 x 75			200 x 50		

All dimensions are in mm unless otherwise shown

### Optional Extras

- **Steel Platform**, Steel Platform A x B = 1150 x 555 H260
- **Roller Platform**, Plastic A x B = 1150 x 555 H264

Special Fork Lengths & Straddle widths available on request, please ask for details

