

LIGHT DUTY STACKER



- Manoeuvrable and easy to use, these stackers lift a capacity of 250kg
- Maximum lift heights of 1830mm to 2450mm
- Wrapover or adjustable fork arrangement
- High quality robust construction
- Designed for use in confined spaces, the twin mast allows entry through standard doorways
- Manual or battery electric powered lift
- 250 kg capacity
- Quality British designed and manufacture

Technical Features:

- Can be used safely at any height
- Fitted with twin castor brakes as standard to prevent the stacker from moving when loading and unloading
- All models fitted with a slow lowering valve to control lowering speed
- Heavy duty castor wheels run on sealed ball races and are fitted with toe guards for additional operator safety
- Available with wrapover or adjustable forks
- Adjustable forks fit between and outside the legs and are manually adjusted
- Battery electric model supplied with heavy duty 70amp/hr traction battery and separate 12 volt charger
- Conforms to European Standard EN1757 part 1

Warnings:

- It is noted that stackers are generally heavy pieces of equipment and should be operated with caution
- Stackers should only be operated on smooth, dry, level floor surfaces
- The rated load of the stacker must not be exceeded as this can be a hazard and cause damage to the stacker
- The load must always be evenly distributed

- Always double check the overall dimensions of the stacker before placing your order to ensure that it can be moved and operated safely within its proposed environment

Technical Specification:

Machine Type			Fixed Wrapover Forks			Adjustable Forks		
B Raised Height	Operation	C/D O/A Height of Machine when forks Raised / Lowered	Reference	Lift Speed	Weight KG	Reference	Lift Speed	Weight KG
1830	Manual	2270/1395	ST-250-1830-M	33/stroke	106	ST-250-1830-M-ADJ	33/stroke	106
1830	Electric	2270/1395	ST-250-1830-E	6 sec / Meter	146	ST-250-1830-E-ADJ	6 sec / Meter	146
2450	Manual	2825 / 1650	ST-250-2450-M	40/stroke	136	ST-250-2450-M-ADJ	40/stroke	136
2450	Electric	2825 / 1650	ST-250-2450-E	6 sec / Meter	200	ST-250-2450-E-ADJ	6 sec / Meter	200
Load Centre		-	270			250		
Free Lift		-	Nil			Nil		
Closed Fork Height		A	90			85		
O/A W x L		E	665 x 1030			665 x 1030		
Fork Length		G	540			500		
Width Across Forks		H	560			635 max		
Fork W x D		-	110 x 50			50 x 20		
Width Between Legs		J	360			360		
Castor Wheels		-	125 dia, 2 braked (Polyurethane)			125 dia, 2 braked (Polyurethane)		
Load Roller Dia x L		-	80 x 40 (Polypropylene)			80 x 40 (Polypropylene)		
Turning Radius		F	950			950		

All dimensions are in mm unless otherwise shown

Optional Extras (Available on all models)

- **Steel Platform*** A x B = 540 x 570
- **Roller conveyor Platform*** Plastic Rollers) A x B = 540 x 570
- **Crane Jib + A = 500**
- **Straddle Width 1100 between legs**

* Fixed fork models only + Adjustable fork models only

